



Figure 2: Task durations under different conditions (median and quartiles)

3 Results

We performed the experiment with 29 participants, which were chosen from different genders, age groups and occupations. Most of them were university students from various disciplines.

A boxplot of the task durations under the different conditions is shown in Figure 2. The results show a significant advantage of 2D and 3DH (3D projection with HCP) over all other display conditions, with no significant difference between the two. Landmarks and stereoscopy had significant negative effects, with 3DSL and 3DSHL performing worst.

There was not as much variation in the number of mistakes as there is for task duration. Noteworthy is only that simple 3D had significantly more mistakes than all other conditions except 3DSH and 3DSL. The only display technology that had a significant positive effect on the number of mistakes was HCP.

The questionnaire asked the participants to rank the display conditions with regard to their perceived efficiency and enjoyment. The results indicate that users' perceived efficiency was correlated with perceived enjoyment, but inversely correlated with the actual efficiency of display technologies as measured by task duration and number of mistakes.

Users were asked to think aloud during the task. Judging from that, the majority of participants believed that HCP was helpful because of adding more realism to the environment (i.e. the ability to see the environment from different view points) without imposing significant strain. The stereoscopic display used in our study caused fatigue and consequently deteriorated the performance. The landmarks added visual clutter and had therefore a negative effect on user performance. Other features such as the spatial arrangement of objects, their colors and a user's familiarity with them seemed to affect recall significantly.

4 Discussion

Unlike the 3D condition where the arrangements were random, the 2D condition always arranged all objects in a regular grid. Furthermore, the objects in the 2D condition were generally bigger than in the 3D conditions and had a clearer contrast to the background. Consequently, layout, object size and contrast were confounding variables that have likely made the 2D condition easier.

Technical problems in the head tracking system caused random jitter and occasional malfunction. Participants found this distracting, and it is a likely reason why participants mostly gave low rankings for HCP. This makes the positive effects of HCP the more surprising, and suggests HCP may perform even better if a more stable technology were used and the participants were more experienced in its use.

5 Conclusion

HCP seems to be a promising technology wrt. spatial memory and should be investigated further. Apparently stereoscopic displays can affect spatial memory negatively, likely because of fatigue. Landmarks need to be designed carefully, as they can have a significant negative effect on spatial memory by adding visual clutter to an environment. Finally, the perceived efficiency of a display technology is not necessarily an indicator of the actual efficiency, but may be more related to enjoyment. As future work, we will modify and replicate the study to remove confounding variables, especially in the 2D condition, and investigate the impact of other stereoscopic displays and types of landmarks.

References

- Cockburn, A. & McKenzie, B. (2001), 3D or not 3D?: evaluating the effect of the third dimension in a document management system, *in* 'Proceedings of the ACM CHI Conference on Human Factors in Computing Systems', ACM, pp. 434–441.
- Jones, W. P. & Dumais, S. T. (1986), 'The spatial metaphor for user interfaces: experimental tests of reference by location versus name', *ACM Transactions on Information Systems (TOIS)* 4(1), 42–63.
- Robertson, G., Czerwinski, M., Larson, K., Robbins, D. C., Thiel, D. & Van Dantzich, M. (1998), Data mountain: using spatial memory for document management, *in* 'Proceedings of the 11th ACM Symposium on User Interface Software and Technology', ACM, pp. 153–162.
- Vicente, K. J., Hayes, B. C. & Williges, R. C. (1987), 'Assaying and isolating individual differences in searching a hierarchical file system', *Human Factors: The Journal of the Human Factors and Ergonomics Society* 29(3), 349–359.